Hazardous Substance/Dangerous Goods Inventory (Safety Data Sheets – SDS)

		"SDS"	records concise health, safe	ty and techni	cal information held for all products used and s	tored by the	organisation			
Chem #	Product Name / UN Number	Approval number, Group Standard or group name and Hazchem code	Hazard classification (UN class & packing group) Cat - category	Current SDS available? Date due	Specific storage and segregation requirements	Container size	Open or closed container?	Gas, liquid or solid	Location	Maximum Amount
1	15W 40 Oil - Penrite		Acute Hazard to the Aquatic Environment - Cat 3 Chronic Hazard to the Aquatic Environment - Cat 3	Yes 21/04/2026	 Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Incompatible with and do not store with, oxidizing agents Store away from sources of heat and/or ignition. 	200 ml 1 litre 5 litres 20 litres	Closed	Liquid	Boss Hire workshops	40 litres
2	2 Stroke Engine Oil – Valvoline	HSR 002606	Skin Corrosion – Cat 2 Specific Target Organ Toxicity following single exposure - Cat 3 – Narcotic Effects	Yes 19/08/2029	 Do not store near ignition sources or in direct sunlight. Do not store with oxidising agents. 	200 ml 1 litre 5 litres	Closed	Liquid	Boss Hire workshops	40 litres
3	5W 30 Oil – Penrite		Assessed as non-toxic	Yes 10/11/2026	 Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Incompatible with and do not store with, oxidizing agents Store away from sources of heat and/or ignition. 	200 ml 1 litre 5 litres 20 litres	Closed	Liquid	Boss Hire workshops	40 litres
4	7 Year Green Coolant	HSR 002606 Group Standard 2006	Acute toxicity – Oral Cat 4 Specific Organ Toxicity (Single Exposure) – Cat 2 Toxic to Reproduction – Cat 1B	Yes 22/05/2027	 Store in original container protected from direct sunlight in a dry, well-ventilated area. Keep separate from incompatible materials (Oxidising substances, strong acids, and strong caustics). Kep away from ignition sources, food and drink. Keep container tightly closed as it absorbs moisture and sealed until ready for use. Keep upright to prevent leaks. 	1 Litre 2.5 Litre 5 Litre 20 Litre	Closed	Liquid	In vehicles	20L
5	80W 90 Oil - Penrite	HSR 002606	Skin Corrosion/Irritation - Cat 2 Eye Damage/Irritation - Cat 2A Acute Hazard to the Aquatic Environment - Cat 3 Chronic Hazard to the Aquatic Environment - Cat 3	Yes 01/09/2028	 Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Incompatible with and do not store with, oxidizing agents Store away from sources of heat and/or ignition. 	200 ml 1 litre 5 litres 20 litres	Closed	Liquid	Boss Hire workshops	40 litres

					•						
6	Alchemis Hybond Epoxy Mortar Hardner UN 3082	HSR 002670 Hazchem 3Z	6.3A, 6.5A, 6.5A, 8.3A, 9.1C	Yes 21/04/2027	•	Do not allow it to freeze. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (Strong oxidizing agents, strong acids and alkali's), food and drink. Keep container tightly closed and sealed until ready for use. Use only in well-ventilated areas. Do not store with oxidizing agents, strong acids or alkalis.	10L	Closed	Solid	In vehicles Camex workshops	20 litres 100 litres
7	Alchemis Hybond Epoxy Mortar Resin UN 3082	HSR 002670 Hazchem 3Z	6.4A, 6.5B, 6.9B, 9.1B.	Yes 22/07/2027	•	Do not allow it to freeze. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from food and drink. Keep separate from oxidizing agents, strong acids and alkali's Keep container tightly closed and sealed until ready for use.	10L	Closed	Solid	In vehicles Camex workshops	20 litres 100 litres
8	Anti-Freeze - Giant		Reproductive Toxicity (Unborn Child) Cat 2 Acute Toxicity (Oral) Cat 4 Specific Target Organ Toxicity - Cat 2, Repeated Exposure (Kidney)	Yes 11/08/2026	•	Store locked up. Store in original tightly closed container. Store away from incompatible materials Incompatible materials: Strong acids. Strong oxidising agents. Nitrates. Peroxides. Chlorates.	500 ml 1 Litre	Closed	Liquid	Boss Hire workshops	4 Litres
9	Automatic Transmission Fluid – ATF DX-III	N/A	Eye Damage/Irritation – Cat A2 Acute hazard to the Aquatic Environment – Cat 3 Chronic Hazard to the Aquatic Environment – Cat 3	Yes 04/01/2028	•	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from food and drink. Keep separate from oxidizing agents	200 ml 1 litre 5 litres 20 litres	Closed	Liquid	Boss Hire workshops	40 litres
10	Bowers Redi Mix Concrete	HSR 002545	8.3A, 6.3A, 6.7A, 6.9A, 9.1D. Skin irritation – Cat 2 Eye damage – Cat 1 Carcinogen – Cat 1	Yes 30/06/27	•	Containers to be kept closed. Keep in cool and dry place. Avoid contact with incompatible substances (Strong acids, ammonium salts, and aluminium metal). Do not sweep, vacuums with filters must be used.	20kg or 25kg	Closed	Solid	Camex workshops In vehicles	1Tonne

11	Brake Cleaner – Wurth UN 1950	Class 2.1 Hazchem 2YE	Aerosols – Cat 1 Skin corrosion/irritation – Cat 2 Specific target organ toxicity single exposure – Cat 3	Yes 22/01/2029	•	Keep away from heat, hot surfaces and other ignition forms. Use in well-ventilated areas. Store locked up. Incompatible with and do not store with, organic peroxide, oxidizing agents, and flammable liquids. Do not store in areas where temperature will exceed 50 degrees Celsius.	200 ml 1 litre 5 litres 20 litres	Closed	Liquid	Boss Hire workshops	40 litres
12	Brake Fluid Super DOT 4 – Penrite		Serious eye damage / irritation – Cat 2A Toxic to reproduction – Cat 2	Yes 30/11/2025	•	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Incompatible with and do not store with, oxidizing agents Store away from sources of heat and/or ignition. Store locked up.	200 ml 1 litre 5 litres 20 litres	Closed	Liquid	Boss Hire workshops	40 litres
13	Conquest	Hazchem 2X	3.1D, 6.1D, 6.3B, 6.4A, 6.5B, 6.9B, 9.1A, 9.2A, 9.3C	Yes 30/05/2027		Store in original container tightly closed and in a locked, dry, cool area away from sources of ignition, seeds, fertilisers and foodstuffs. Storage must be in accordance with NZS 8409 Management of Agrichemicals. Do not store near heat or flame. Stores containing 100L of CONQUEST require secondary containment and are subject to signage, and more than 100L require emergency response plans. Stores exceeding 500 litres of this substance must have at least 2 fire extinguishers. not store with HSNO Class 1, 2, 3.2, 4 or 5 ostances.	20 litres	Closed	Liquid	In vehicles	40 Litres
14	Country mile 510 – Glyphosate		6.4A, 9.1B Serious eye damage – Cat 1 Hazardous to the aquatic environment chronic – Cat 2	Yes 09/09/2027	•	Store in original container, tightly closed, in a secure, dry, cool and well-ventilated area and avoid direct sunlight. Store away from foodstuffs, fertilisers or seeds. Storage must be in accordance with NZS 8409 Management of Agrichemicals. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Stores containing 1000 litres or more of Country Mile Glyphosate 510 require secondary containment, signage and an emergency response plan. Country Mile Glyphosate 510 should only be stored and applied in plastic or plastic lined containers, aluminum, brass, copper, stainless steel or fiberglass containers.	20 litres	Closed	Liquid	In vehicles	40 Litres

15	CRC Pipe Cement UN 1133	Hazchem 3YE	3.1B, 6.1C(Dermal), 6.1D(Oral), 6.3A, 6.4A, 6.7B, 6.9B, 9.3C Flammable Liquids Cat 2 Acute Toxicity (Oral) Cat 4 Acute Toxicity (Dermal) Cat 4 Skin Corrosion/Irritation Cat 2 Serious Eye Damage/Eye Irritation Cat 2 Carcinogenicity Cat 2 Specific Target Organ Toxicity - Repeated Exposure Cat 2	Yes 10/03/2028	•	Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately. Check for bulging containers. Vent periodically Always release caps or seals slowly to ensure slow dissipation of vapours Do not allow clothing wet with material to stay in contact with skin	500ml 4 Litre	Closed	Liquid	In vehicles	10L
16	Denso MP Primer		Assessed as non-toxic	Yes 09/05/2028	•	Incompatible with and do not store with, oxidizing agents or acids Store away from sources of heat and/or ignition.	200 ml 1 litre 5 litres 20 litres	Closed	Liquid	Boss Hire workshops	40 litres
17	Diesel		3.1D, 6.1E, 6.3B, 6.7B, 9.1B							Camex yards	10000 Litres
I	UN3082		Skin irritation – Cat 3	,	1		10,000	,	1	Fuel tankers	1500 Litres
		Hazchem 3Z	Aspiration toxicant – Cat 1 Carcinogen – Cat 2 Acute aquatic toxicant – Cat 2	Yes 02/04/2027	• •	Store in a well-ventilated place. Keep cool. Store locked up	10,000 Litre 1500 Litre 20 Litre 5 Litre	Closed	Liquid	In vehicles	100 litres
			Chronic aquatic toxicant – Cat								
18	Dricon Mortar	HSR 002545 Group Standard 2017	6.3A, 8.3A, 6.7A, 6.9A, 9.1D Skin irritant – Cat 2 Eye damage – Cat 1 Carcinogenicity – Cat 1	Yes 30/07/2028	•	Keep out of reach of children. Keep the container tightly closed in a dry, well- ventilated place. Must not be stored with strong acids.	20kg or 25kg	Closed	Solid	Camex workshops In vehicles	1Tonne

19	Enviro-C Dechlorination Tablets	Not classified	Class 9	Yes 30/01/2029	•	Store in a cool, dry, well-ventilated area away from oxidizers, strong acids and string bases, foodstuffs, and direct sunlight. Ensure container lids tightly closed.	10kg	Closed	Solid	In vehicles	10kg
20	Focus Shock and Clear UN 3077	Hazchem 2Z	Serious eye damage/irritation 1 Aquatic Acute 1 Aquatic Chronic 1 Acute Toxicity (Oral) 4 Acute toxicity – Oral Category 4	No – Unable to obtain	•	Store in a cool, dry, well-ventilated area away from oxidizers, strong acids and string bases, foodstuffs, and direct sunlight. Ensure container lids tightly closed.	500g or 20L	Closed	Solid or Liquid	Storage Container, Back of Utes	20L
21	Gorilla Manhole Sealant UN 1950	Not classified	Class 9	Yes 30/09/2023	•	Store in a cool, dry, well-ventilated area away from oxidizers, strong acids and string bases, foodstuffs, and direct sunlight. Ensure container lids tightly closed. Not to be stored with copper, zinc, aluminum or their alloys.	500g	Closed	Liquid	Storage Container, Back of Utes	50kg
22	IPA Electronic Cleaner Aerosol - Chemz	Hazchem 2YE	2.1.2A – Aerosol Cat 1 6.4A – Eye irritation Cat 2	Yes 15/11/2027	•	Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well-ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.	100 ml	Closed	Gas	Camex workshops	10 kg's
23	Liquid Chlorine – Sodium Hypochlorite Solution UN 1791	Hazchem 2R HSR 004692	8.2C, 8.3A, 9.1A, 9.1D. Substances that are corrosive to dermal tissue Substances that are corrosive to ocular tissue Substances that are very ecotoxic in the aquatic environment Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal action - Algae	Yes 24/02/2029	•	Store in cool place and out of direct sunlight. Store locked up. Do not store with acids, metals, metal salts, peroxides, reducing agents, and ethylene, diamine tetra-acetic acid.	20L	Closed	Liquid	Camex workshops In vehicles	40L
24	Manhole Sealant – Soudal		Assessed as non-toxic	Yes 30/06/2026	•	No restrictions or specific requirements	5kg boxes	Closed	Solid	On vehicles	10 kg's

										Camex workshops	50kg's
25	Marley Gold Cement UN 1133	HSR 002662	6.3A, 8.3A, 6.5B, 6.9B, 3.1B Flammable liquids – Cat 2 Skin corrosion/irritation Cat 2 Serious eye damage/eye irritation Cat 1 Skin Sensitization Cat 1 Specific target organ toxicity (Single exposure) Cat 3	Yes 18/04/2028	•	Store in cool and well-ventilated place. Protect from moisture. Do not store with strong acids or bases.	250 ml 500 ml 1 Litre 4 Litre	Closed	Liquid	In vehicles	4L
26	Marley Joint Primer CF500 UN 1993	HSR 002662	6.4A, 6.9B, 3.1B Flammable liquids Cat 2 Serious eye damage/eye irritation Cat 2 Specific target organ toxicity (Single exposure) Cat 3	Yes	•	Store in cool and well-ventilated place. Protect from moisture. Do not store with strong acids or bases. Keep away from ignition sources.	250ml, 500ml, 1 Litre, 4 Litre	Closed	Liquid	In vehicles	4L
27	Oatey Pipe Joint Lubricant	Not classified	9 Serious Eye Damage/Eye Irritation Cat 2B	Yes 12/07/2026	•	Do not store with strong oxidizing agents or strong bases.	1kg 4 Litre 20 Litre	Closed	Liquid	In vehicles	20 Litre
28	Petrol 91 Unleaded UN1203	Hazchem 3YE	3.1A, 6.1E, 6.3B, 6.7B, 9.1B Skin irritation – Cat 3 Aspiration toxicant – Cat 1 Carcinogen – Cat 2 Acute aquatic toxicant – Cat 2 Chronic aquatic toxicant – Cat 2	Yes 20/04/2027	•	Store in a cool, dry, well-ventilated area away from sources of ignition, oxidizing agents, strong acids, foodstuffs, and clothing. This product must never be stored in buildings occupied by people. Small volumes may be stored in a suitably designed portable container. Ensure container lids tightly closed. Signage required if storing more than 50 Litres	5 Litre 10 Litre 20 Litre	Closed	Liquid	In vehicles	50L
21	Plumbers Clear Glue – Plumma's Type N Clear	Hazchem 3YE	Flammable Liquids Cat 2, Serious Eye Damage/Eye Irritation Cat 2A,	Yes 29/05/2028	•	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area.	125 ml 250 ml 500ml	Closed	Liquid	Camex workshops	20 Litres

	UN 1133		Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Cat 3, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Cat 3		•	Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. Keep cool Keep locked up. Avoid strong bases. Avoid reaction with oxidising agents	1 Litre 5 Litre			In vehicles	10 Litres
22	Portland Cement and Blends – Holcim	Group Standard 2017	6.3A, 6.5B, 8.2C, 8.3A, 6.9B, 6.1E, Skin irritation Cat 2 Skin sensitisation Cat 1 Skin corrosion Cat 1C Serious eye damage Cat 1 Specific target organ toxicity – repeated exposure Cat 2 Specific target organ toxicity – single exposure Cat 3 respiratory Tract irritation	Yes 01/11/2026	•	Store locked up. Store in a well-ventilated area. Keep container / package tightly closed. Keep dry and store off the ground.	20kg or 25kg	Closed	Solid	Camex workshops In vehicles	1Tonne
23	Power Armour 2 Stroke Semi Synthetic - Valvoline		Assessed as non-toxic	Yes 09/05/2025	•	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Incompatible with and do not store with, oxidizing agents Store away from sources of heat and/or ignition.	500 ml 1 Litre	Closed	Liquid	Boss Hire workshops	4 Litres
24	Pulse Penetrant – Nufarm UN 3082	Hazchem 2X	 6.1D acute toxicant, 6.4A eye irritant, 6.9B target organ toxicant, 9.1B aquatic toxicant 	Yes 30/12/2026	•	Store in the closed, original container in a cool, well-ventilated area. Do not store for prolonged periods in direct sunlight. Stores containing 1,000L of Pulse Penetrate require secondary containment and are subject to signage, and more than 1,000L require emergency response plans.	20 Litres	Closed	Liquid	On vehicles	100 Litres
25	Rando HD 46 – Hydraulic Oil - Caltex		Assessed as non-toxic	Yes 15/09/2025	•	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Incompatible with and do not store with, oxidizing agents Store away from sources of heat and/or ignition.	200 ml 1 litre 5 litres 20 litres	Closed	Liquid	Boss Hire workshops	40 litres

26	Renolit LXMO 2 - Fusch		Assessed as non-toxic	Yes 02/02/2029	•	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Incompatible with and do not store with, oxidizing agents Store away from sources of heat and/or ignition.	200 ml tubes 5 kg boxes	Closed	Liquid	Boss Hire workshops Camex workshops	60 kg's 60 kg's
27	Residual herbicide UN 3082	Hazchem 3Z HSR007866	 6.1E, 6.4A, 6.8B, 6.9B, 9.1A, 9.2A, 9.3C May be harmful if swallowed Causes serious eye irritation Suspected of damaging fertility or the unborn child May cause damage to organs through prolonged or repeated exposure Very toxic to aquatic life with long lasting effects 	Yes 30/07/2030	•	Must be kept secured. Do not exceed the maximum application rate of 25 L/ha. Do not apply more than twice per year. Signage is required for more than 100 litres An emergency response plan is required for more than 100 litres Secondary containment is required for more than 100 litres Segregation from incompatible substances is not applicable.	20 litres	Closed	Liquid	In vehicles	40 Litres
28	Soppec Construction Fluo TP Spray Marker UN 1415		Extremely flammable aerosol – Cat 1 Gas under pressure	Yes 21/09/2027	•	May displace oxygen and cause rapid suffocation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated area. Keep container tightly closed. Not to be stored with oxidizing materials	500g cans 6 kg boxes	Closed	Gas	On vehicles Camex workshops	12 kg's 150 kg's
29	Ultra-Duty Grease	HSR002606	Serious Eye Damage/Irritation - Cat 1 Long Term Hazards to the Aquatic Environment - Cat 3	Yes 19/03/2029	•	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Incompatible with and do not store with, oxidizing agents Store away from sources of heat and/or ignition.	200 ml tubes 5 kg boxes	Closed	Liquid	Boss Hire workshops	60 kg's

30	Vircuclear – Surface Sanitiser	HSR002530	 6.1E (O) May be harmful if swallowed. 6.4A Causes serious eye irritation. 8.3A Causes serious eye damage. 9.1D (Slightly Harmful) Harmful to aquatic life. 	Yes 11/03/2025	Store in original container or suitable dispenser in a well-ventilated place. Keep cool. When not in use, store in a cool, dry, dark, ideally lockable location. Direct sunlight may result in colour fading.	250 g 500 g	Closed	Solid	In vehicles	1 kg
31				No – As waste oil is		60 litres			Boss Hire workshops	60 litres
	Waste oil – Bulk mixed	- Bulk HSR002606 - Cat 3 - Chronic Hazard to the Aquatic Environment - Cat 3		an accumulatio n of all oils. Highest risk SDS used for assessment, being Penrite 80W90	 Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Incompatible with and do not store with, oxidizing agents Store away from sources of heat and/or ignition. 	1000 litres	Closed	Liquid	Outside in Yard beside water blaster shed and against western wall at south end.	1000 litres
	etion guide and action eted Safety Data Shee		all products and the information	on, health risks	s and the directive to use protective equipment have	been conve	yed to employ	ees and r	ecorded in the	Safety

Training and Competency Register

For hazardous substance compliance information call EPA on 0800 225 537.

Hazardous Substances Information

We will ensure that hazardous substances that are stored or handled on site are clearly labelled, have an SDS (Substances Data Sheet) from suppliers for each product and will record these in the company Hazardous Substances Register.

Hazardous Substances may cause long term effects and significant risks to Workers if not stored and handled correctly. We will ensure all Workers who may be exposed to any hazardous substance during any work activity are provided with appropriate personal protective equipment, information and training on the nature of the hazard and the means of reducing or controlling any exposure to the hazardous substance.

Full Detailed list of all Camex Hazardous Substances can be found online through Dropbox or alternatively Camex is utilising the Hazardous Substances Calculator Tool provided by WorkSafe https://www.hazardoussubstances.govt.nz/calculator#C9A61C

Under HSNO legislation, certain substances and/or volume quantities must be under the control of an 'Approved Handler'. We will ensure trained Approved Handlers will be on site if required.

Some flammable or oxidising substances at on our workplace may also require a Location Test Certificate. We will ensure trained Location Test Certificates are achieved and current if required.

All hazardous substances and containers must be disposed in accordance with legislation or the manufacturer's instructions or technical support documents.

Other hazardous substances such as Asbestos containing materials (ACM), Contaminated Substances and/or Soils may be found in our area of works.

If any of these materials are found work will stop and the area cordoned off until an approved plan is in place.

In the case of ACM or contaminated ground an independent assessor will be called into site to test the substance and a report made.

If the substance is tested positive all materials will be removed from site to an approved dump site. In the case or ACM this will either be under supervision or by an approved removal specialist.

More information is available through the Environmental Protection Authority at <u>http://www.epa.govt.nz</u> and Codes of Practice are available from Worksafe at <u>www.worksafe.govt.nz</u>